

Светоотражающие фотоэлектрические датчики стандартные

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>



PRK46C.1/6G-M12

Polarized retro-reflective photoelectric sensor

Series: 46C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/4X-2000-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/4-200-M8.3

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK53CL1.A3/LG-5000

Polarized retro-reflective photoelectric sensor

Series: 53C, 53C

Operating range, max.: 0 ... 2 m **Design:** Cubic, Cubic

Light source: Laser, Red, Laser, Red



SET PRK5B/4X-200-M8+TKS40x60.A

Polarized retro-reflective photoelectric sensor set

Series: 5B

Operating range, max.: 0.02 ... 2.8 m **Design:** Cubic

Light source: LED, Red

PRK5B/4X-800-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/4X-400-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



SET PRK5B/4X-200-M8+BTU200MVKT

Polarized retro-reflective photoelectric sensor set

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/PX-1000-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



SET PRK5B.D/4X-200-M12+BTU200M

Polarized retro-reflective photoelectric sensor set

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



RK46C.DL3/LP-200-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.55 ... 1.5 m **Design:** Cubic

Light source: LED, Red



RK46C.DXL3P2/LP-200-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.4 ... 2 m **Design:** Cubic

Light source: LED, Red



PRK5B.M1/PX-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.03 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5B.M1/4

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.03 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK36.D/N

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36/N

Polarized retro-reflective photoelectric sensor

Series: 36

Operating range, max.: 0.3 ... 17 m **Design:** Cubic

Light source: LED, Red



PRK25C/PX-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.05 ... 10 m **Design:** Cubic

Light source: LED, Red



PRK5B/4X-2000-M8

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B/PX-2000-M8

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK55C.A3/LG-5000

Polarized retro-reflective photoelectric sensor

Series: 55C, 55C
Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic
Light source: LED, Red, LED, Red



SET PRK5B/4+TKS 40x60.A

Polarized retro-reflective photoelectric sensor set


Series: 5B
Operating range, max.: 0.02 ... 2.8 m **Design:** Cubic
Light source: LED, Red



PRK5B.D/4X-200-M8

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.04 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK53CL1.A3/LT-M8

Polarized retro-reflective photoelectric sensor

Series: 53C, 53C
Operating range, max.: 0 ... 2 m **Design:** Cubic, Cubic

Light source: Laser, Red, Laser, Red



SET PRK5B/4X-200-M12+BTU200MVKT

Polarized retro-reflective photoelectric sensor set

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK53CL1.XA3/LG-M8

Polarized retro-reflective photoelectric sensor

Series: 53C, 53C

Operating range, max.: 0 ... 2 m **Design:** Cubic, Cubic

Light source: Laser, Red, Laser, Red



PRK5B.D/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5.M3/4P-200-M8

Polarized retro-reflective photoelectric sensor

Series: 5

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5B.M1/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.03 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5B/P-M8.3

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/4X-1000-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5B.M1/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.03 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5B/4X-600-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red

PRK5B/NX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/NX-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/PX-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B.M1/2

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.03 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5B.M1/2X-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.03 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5B.M1/4X-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.03 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK55CL1.A3/LG-200-M12

Polarized retro-reflective photoelectric sensor

Series: 55C, 55C

Operating range, max.: 0 ... 2 m **Design:** Cubic, Cubic

Light source: Laser, Red, Laser, Red



PRK55CL1.A3/LG-M8

Polarized retro-reflective photoelectric sensor

Series: 55C, 55C

Operating range, max.: 0 ... 2 m **Design:** Cubic, Cubic

Light source: Laser, Red, Laser, Red



PRK55C.A3/LG-200-M12

Polarized retro-reflective photoelectric sensor

Series: 55C, 55C

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK55C.A3/LG-M8

Polarized retro-reflective photoelectric sensor

Series: 55C, 55C

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red

PRK55C/LG-200-M12

Polarized retro-reflective photoelectric sensor

Series: 55C, 55C

Operating range, max.: 0.02 ... 5 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK55C/LG-M8

Polarized retro-reflective photoelectric sensor

Series: 55C, 55C

Operating range, max.: 0.02 ... 5 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK53CL1.A3/LG-M8

Polarized retro-reflective photoelectric sensor

Series: 53C, 53C

Operating range, max.: 0 ... 2 m **Design:** Cubic, Cubic

Light source: Laser, Red, Laser, Red



PRK53C.A3/LG-M8

Polarized retro-reflective photoelectric sensor

Series: 53C, 53C

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



RK46C.DXL3/4W-M12P1

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.4 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK28/4X-200-M8

Polarized retro-reflective photoelectric sensor

Series: 28

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK36.D/2

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/P

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/4

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/NX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/2X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red

PRK36.D/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/NX-M12

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/2X-M12

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/PX-M12

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36.D/4X-M12

Polarized retro-reflective photoelectric sensor

Series: 36, 36

Operating range, max.: 0.3 ... 11 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK36/2

Polarized retro-reflective photoelectric sensor

Series: 36
Operating range, max.: 0.3 ... 17 m **Design:** Cubic
Light source: LED, Red



PRK36/P

Polarized retro-reflective photoelectric sensor

Series: 36
Operating range, max.: 0.3 ... 17 m **Design:** Cubic
Light source: LED, Red



PRK36/4

Polarized retro-reflective photoelectric sensor

Series: 36
Operating range, max.: 0.3 ... 17 m **Design:** Cubic
Light source: LED, Red



PRK36/NX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 36
Operating range, max.: 0.3 ... 17 m **Design:** Cubic
Light source: LED, Red



PRK36/2X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 36
Operating range, max.: 0.3 ... 17 m **Design:** Cubic
Light source: LED, Red

PRK36/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 36
Operating range, max.: 0.3 ... 17 m **Design:** Cubic



PRK36/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 36

Operating range, max.: 0.3 ... 17 m **Design:** Cubic

Light source: LED, Red



PRK36/NX-M12

Polarized retro-reflective photoelectric sensor

Series: 36

Operating range, max.: 0.3 ... 17 m **Design:** Cubic

Light source: LED, Red



PRK36/2X-M12

Polarized retro-reflective photoelectric sensor

Series: 36

Operating range, max.: 0.3 ... 17 m **Design:** Cubic

Light source: LED, Red



PRK36/PX-M12

Polarized retro-reflective photoelectric sensor

Series: 36

Operating range, max.: 0.3 ... 17 m **Design:** Cubic

Light source: LED, Red



PRK36/4X-M12

Polarized retro-reflective photoelectric sensor

Series: 36

Operating range, max.: 0.3 ... 17 m **Design:** Cubic

Light source: LED, Red



RK46C.DL3/2N-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.55 ... 1.5 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/NX-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/2X-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/N

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/2

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red

PRK5B.D/PX-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic



PRK5B.D/4X-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/P

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5B.D/4

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.04 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3C.BA3/2N

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK5B.1/PX-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B.1/4X-M8

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B/4X-800-M12

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



SET PRK23/PX-M8TKS50x50.1

Polarized retro-reflective photoelectric sensor

Series: 23
Operating range, max.: 0.1 ... 2.5 m **Design:** Cubic
Light source: LED, Red



PRK3C/PX-M8

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0.1 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK25CL1.1/2N-M8

Polarized retro-reflective photoelectric sensor

Series: 25C
Operating range, max.: 0.2 ... 20 m **Design:** Cubic
Light source: Laser, Red



PRK23/P

Polarized retro-reflective photoelectric sensor

Series: 23
Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5B.1/P

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B.1/4

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B.1/N

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B.1/2

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B/4X-200-M8.1

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red

PRK5B/P-200-M8.3

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic



PRK5B/4-200-M8.3

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/2X-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/4X-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/4X-200-M8

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/4X-350-M12

Polarized retro-reflective photoelectric sensor

Series: 5B

Operating range, max.: 0.02 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK5B/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B/2X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B/2

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B/4

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK5B/P

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic
Light source: LED, Red

PRK5B/N

Polarized retro-reflective photoelectric sensor

Series: 5B
Operating range, max.: 0.02 ... 5 m **Design:** Cubic



PRK28/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 28

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK46C/4X-M12

Polarized retro-reflective photoelectric sensor

Series: 46C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK23/PX-200-M8

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/4X-200-M8

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



SET PRK23/PX-200-M8TKS50x50.1

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 2.5 m **Design:** Cubic

Light source: LED, Red



SET PRK23/4X-200-M8TKS50x50.1

Polarized retro-reflective photoelectric sensor

Series: 23
Operating range, max.: 0.1 ... 2.5 m **Design:** Cubic
Light source: LED, Red



SET PRK23/4X-M8TKS50x50.1

Polarized retro-reflective photoelectric sensor

Series: 23
Operating range, max.: 0.1 ... 2.5 m **Design:** Cubic
Light source: LED, Red



SET PRK46C.D/4P-M12BTU300M-D12

Polarized retro-reflective photoelectric sensor set

Series: 46C
Operating range, max.: 0.1 ... 16 m **Design:** Cubic
Light source: LED, Red



RK46C.DL3/4P-200-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C
Operating range, max.: 0.55 ... 1.5 m **Design:** Cubic
Light source: LED, Red



RK46C.DL3/4P-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C
Operating range, max.: 0.55 ... 1.5 m **Design:** Cubic
Light source: LED, Red

PRK3C/4P

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0.1 ... 5 m **Design:** Cubic



PRK3CL1.A3/6-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK318B/2N-5000

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK3C/P-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK3C/PX-200-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK3C/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK412B/N

Polarized retro-reflective photoelectric sensor

Series: 412B

Operating range, max.: 0.02 ... 1.8 m **Design:** Cylindrical

Light source: LED, Red



PRK412B/2

Polarized retro-reflective photoelectric sensor

Series: 412B

Operating range, max.: 0.02 ... 1.8 m **Design:** Cylindrical

Light source: LED, Red



PRK412B/NX-M12

Polarized retro-reflective photoelectric sensor

Series: 412B

Operating range, max.: 0.02 ... 1.8 m **Design:** Cylindrical

Light source: LED, Red



PRK412B/2X-M12

Polarized retro-reflective photoelectric sensor

Series: 412B

Operating range, max.: 0.02 ... 1.8 m **Design:** Cylindrical

Light source: LED, Red




PRK412B/P

Polarized retro-reflective photoelectric sensor

Series: 412B

Operating range, max.: 0.02 ... 1.8 m **Design:** Cylindrical

Light source: LED, Red



PRK412B/4

Polarized retro-reflective photoelectric sensor

Series: 412B

Operating range, max.: 0.02 ... 1.8 m **Design:** Cylindrical



PRK412B/PX-M12

Polarized retro-reflective photoelectric sensor

Series: 412B

Operating range, max.: 0.02 ... 1.8 m **Design:** Cylindrical

Light source: LED, Red



PRK412B/4X-M12

Polarized retro-reflective photoelectric sensor

Series: 412B

Operating range, max.: 0.02 ... 1.8 m **Design:** Cylindrical

Light source: LED, Red



PRK25CL1.1/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic

Light source: Laser, Red



PRK25CL1.1/2N

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic

Light source: Laser, Red



PRK25CL1.1/4P

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic

Light source: Laser, Red



PRK25CL1.1/4P-M8

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic

Light source: Laser, Red



PRK25CL1.1/28-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic

Light source: Laser, Red



PRK25CL1.1/48-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic

Light source: Laser, Red



PRK25CL1.1/PX-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic

Light source: Laser, Red



PRK25CL1.1/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic

Light source: Laser, Red

PRK25CL1.1/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.2 ... 20 m **Design:** Cubic



PRK25C/6G-100-M8

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.05 ... 10 m **Design:** Cubic

Light source: LED, Red



PRK25C/48-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.05 ... 10 m **Design:** Cubic

Light source: LED, Red



PRKL 53/6D.22,5000

Polarized retro-reflective photoelectric sensor

Series: 53

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK23/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/PX-M8

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/4X-M8

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/NX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/NX-M8

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/N

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red

PRK23/2X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m



PRK23/2X-M8

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/4

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK23/2

Polarized retro-reflective photoelectric sensor

Series: 23

Operating range, max.: 0.1 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/6T-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3CL1.A3/6T-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK25C/4W-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.05 ... 10 m **Design:** Cubic

Light source: LED, Red



PRK3C/6G-200-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/2N-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK15/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 15

Operating range, max.: 0.05 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK3CL1.BA3/4P-200-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/4P-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK15/N

Polarized retro-reflective photoelectric sensor

Series: 15
Operating range, max.: 0.05 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK15/NX-M12

Polarized retro-reflective photoelectric sensor

Series: 15
Operating range, max.: 0.05 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK15/P

Polarized retro-reflective photoelectric sensor

Series: 15
Operating range, max.: 0.05 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK15/PX-M12

Polarized retro-reflective photoelectric sensor

Series: 15
Operating range, max.: 0.05 ... 8 m **Design:** Cubic
Light source: LED, Red



PRKL 53/6.22,5000

Polarized retro-reflective photoelectric sensor

Series: 53
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red

PRK3C.1/6G

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0.1 ... 5 m **Design:** Cubic



PRK3C/6-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK3C.B1/6G-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK3C.1/6G-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK3C.B/6G-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK3C/6G-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0.1 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK3C/6G

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0.1 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK3C.B/6G-M8

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0.1 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK3C/6G-M8

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0.1 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK3CL1.A3/P-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red



PRK3CL1.A3/4-200-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red

PRK3C.A3/4-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic



PRK3CL1.A3/PT-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK46C/LP-M12

Polarized retro-reflective photoelectric sensor

Series: 46C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



SET PRK46C/4P-M12+BTU46.25

Polarized retro-reflective photoelectric sensor set

Series: 46C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



RK46C.DXL3P2/4P-200-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.4 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3CL1.A3/2-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK18B.XT3/P4-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK3C.A3/2N

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3CL1.BA3/2N

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



RK46C.DXL3/PX-200-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.4 ... 4 m **Design:** Cubic

Light source: LED, Red



RK46C.DXL3P2/4P-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.4 ... 4 m **Design:** Cubic

Light source: LED, Red

PRK49C.1/2N-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic



PRK49C.1/4P-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK49C/4P-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK15/2X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 15

Operating range, max.: 0.05 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK15/2

Polarized retro-reflective photoelectric sensor

Series: 15

Operating range, max.: 0.05 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK15/2X-M12

Polarized retro-reflective photoelectric sensor

Series: 15

Operating range, max.: 0.05 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK15/4

Polarized retro-reflective photoelectric sensor

Series: 15
Operating range, max.: 0.05 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK15/4X-M12

Polarized retro-reflective photoelectric sensor

Series: 15
Operating range, max.: 0.05 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK25C/2N-200-M12

Polarized retro-reflective photoelectric sensor

Series: 25C
Operating range, max.: 0.05 ... 10 m **Design:** Cubic
Light source: LED, Red



PRK25C/2N-M8

Polarized retro-reflective photoelectric sensor

Series: 25C
Operating range, max.: 0.05 ... 10 m **Design:** Cubic
Light source: LED, Red



PRK25C/2N

Polarized retro-reflective photoelectric sensor

Series: 25C
Operating range, max.: 0.05 ... 10 m **Design:** Cubic
Light source: LED, Red

PRK25C/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 25C
Operating range, max.: 0.05 ... 10 m **Design:** Cubic



PRK25C/4P-200-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.05 ... 10 m **Design:** Cubic

Light source: LED, Red



PRK25C/4P-M8

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.05 ... 10 m **Design:** Cubic

Light source: LED, Red



PRK25C/4P

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.05 ... 10 m **Design:** Cubic

Light source: LED, Red



PRK25C/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 25C

Operating range, max.: 0.05 ... 10 m **Design:** Cubic

Light source: LED, Red



PRK3CL1.BA3/LP-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.BA3/4P-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red



PRK3CL1.BA3/4P

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red



PRK3CL1.BA3/4P-M8

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red



PRK3CL1.BA3/4T

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red



PRK3CL1.BA3/4T-M8

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red

PRK3CL1.A3/LP-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic



PRK3CL1.A3/LP

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/LP-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/4P-200-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/4P-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/4P

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/4-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red



PRK3C.BA3/4P-200-M8

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK3C.BA3/4P-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK3C.BA3/4P

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK3C.BA3/4P-M8

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red

PRK3C.BA3/4T-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic



PRK3C.BA3/4T-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/4P-200-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/4P-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/4P

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/4P-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/LP

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:**

Cubic

Light source: LED, Red



PRK3C.A3/4T-200-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK49C.UC1/TS-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



RK46C.DXL3/PX-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.4 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK328.W3/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 328

Operating range, max.: 0.02 ... 4 m **Design:**

Cylindrical

Light source: LED, Red



PRK28/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 28

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/LP-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK3C.A3/4-200-M8.3

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



RK46C.DXL3/LP-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.4 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK318B/PX-M12

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK18B.TT3/6G-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red

PRK49C.UCH/M4-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.3 ... 24 m **Design:** Cubic



PRK49C.UCH/TS-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK3CL1.A3/4T-200-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/4T-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/4T

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3CL1.A3/4T-M8

Polarized retro-reflective photoelectric sensor

Series: 3C

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK3C.A3/4T-200-M12

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK3C.A3/4T

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK3C.A3/4T-M8

Polarized retro-reflective photoelectric sensor

Series: 3C
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRKL 8/44.91-S12

Polarized retro-reflective photoelectric sensor

Series: 8
Operating range, max.: 0 ... 19 m **Design:** Cubic
Light source: Laser, Red



PRK49C.UCD1/TS

Polarized retro-reflective photoelectric sensor

Series: 49C
Operating range, max.: 0.1 ... 16 m **Design:** Cubic
Light source: LED, Red

PRK49C.UCD1/TS-TB

Polarized retro-reflective photoelectric sensor

Series: 49C
Operating range, max.: 0.1 ... 16 m **Design:** Cubic



PRK49C.UC/M4-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.3 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK49C.UC1/M4

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.3 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK49C.UC1/M4-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.3 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK49C.UC/TS-TB

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK49C.UC1/TS

Polarized retro-reflective photoelectric sensor

Series: 49C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK46C/4W-M12

Polarized retro-reflective photoelectric sensor

Series: 46C
Operating range, max.: 0.1 ... 24 m **Design:** Cubic
Light source: LED, Red



PRK46C/2N

Polarized retro-reflective photoelectric sensor

Series: 46C
Operating range, max.: 0.1 ... 24 m **Design:** Cubic
Light source: LED, Red



PRK46C/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 46C
Operating range, max.: 0.1 ... 24 m **Design:** Cubic
Light source: LED, Red



PRK46C/PX-200-M12

Polarized retro-reflective photoelectric sensor

Series: 46C
Operating range, max.: 0.1 ... 24 m **Design:** Cubic
Light source: LED, Red



PRK46C/48-M12

Polarized retro-reflective photoelectric sensor

Series: 46C
Operating range, max.: 0.1 ... 24 m **Design:** Cubic
Light source: LED, Red

PRK46C.1/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 46C
Operating range, max.: 0.1 ... 24 m **Design:** Cubic



PRK46C/4P-200-M12

Polarized retro-reflective photoelectric sensor

Series: 46C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK46C/4P

Polarized retro-reflective photoelectric sensor

Series: 46C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK46C/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 46C

Operating range, max.: 0.1 ... 24 m **Design:** Cubic

Light source: LED, Red



PRK18B.TT3/P4-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



RK46C.DXL3/2N-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C

Operating range, max.: 0.4 ... 4 m **Design:** Cubic

Light source: LED, Red



RK46C.DXL3/4P-200-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C
Operating range, max.: 0.4 ... 4 m **Design:** Cubic
Light source: LED, Red



RK46C.DXL3/4P

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C
Operating range, max.: 0.4 ... 4 m **Design:** Cubic
Light source: LED, Red



RK46C.DXL3/4P-M12

Unpolarized retro-reflective photoelectric sensor

Series: 46C, 46C
Operating range, max.: 0.4 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK18B.XT2/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B
Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic
Light source: LED, Red, LED, Red



PRK18B.XT3/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B
Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic
Light source: LED, Red, LED, Red

PRK18B.XTT3/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B
Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic



PRK328.3/2N

Polarized retro-reflective photoelectric sensor

Series: 328

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK328.3/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 328

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK328.3/4P

Polarized retro-reflective photoelectric sensor

Series: 328

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK328.3/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 328

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK328.W3/2N

Polarized retro-reflective photoelectric sensor

Series: 328

Operating range, max.: 0.02 ... 4 m **Design:** Cylindrical

Light source: LED, Red



PRK328.W3/4P

Polarized retro-reflective photoelectric sensor

Series: 328

Operating range, max.: 0.02 ... 4 m **Design:** Cylindrical

Light source: LED, Red



PRK328.W3/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 328

Operating range, max.: 0.02 ... 4 m **Design:** Cylindrical

Light source: LED, Red



PRK28.3/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 28

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK28/4P-200-M12

Polarized retro-reflective photoelectric sensor

Series: 28

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK 53/6.22,5000

Polarized retro-reflective photoelectric sensor

Series: 53

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red

PRK18B.FXT3/2T-6000

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic



PRK18B.TT3/LP-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.TT3/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.TT3/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.TT3/2N-6000

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK28/2N

Polarized retro-reflective photoelectric sensor

Series: 28

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK28/4P

Polarized retro-reflective photoelectric sensor

Series: 28
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK28/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 28
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



RK18B.T2/4P-M12

Unpolarized retro-reflective photoelectric sensor

Series: 18B, 18B
Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic
Light source: LED, Red, LED, Red



RK18B.T2/2N-M12

Unpolarized retro-reflective photoelectric sensor

Series: 18B, 18B
Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic
Light source: LED, Red, LED, Red



RK18B.1/4P-M12

Unpolarized retro-reflective photoelectric sensor

Series: 18B, 18B
Operating range, max.: 0 ... 6 m **Design:** Cubic, Cubic
Light source: LED, Red, LED, Red

RK18B.1/4P-6000

Unpolarized retro-reflective photoelectric sensor

Series: 18B, 18B
Operating range, max.: 0 ... 6 m **Design:** Cubic,
Cubic



RK18B.1/2N-M12

Unpolarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 6 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



RK18B.1/2N-6000

Unpolarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 6 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.FXT3/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.FXT3/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 3 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.T3/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.T3/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK318B.W/2N

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4 m **Design:** Cylindrical

Light source: LED, Red



PRK 2/42

Polarized retro-reflective photoelectric sensor

Series: 2

Operating range, max.: 0.07 ... 3.5 m **Design:** Cubic

Light source: LED, Red



PRK 55/6.22,200-S12

Polarized retro-reflective photoelectric sensor

Series: 55

Operating range, max.: 0 ... 4 m **Design:** Cubic

Light source: LED, Red



PRK 96K/N-1380-46

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK 8/66-S12

Polarized retro-reflective photoelectric sensor

Series: 8

Operating range, max.: 0.1 ... 6.4 m **Design:** Cubic

Light source: LED, Red



PRK18B.T2/4X-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.T2/NX-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.T2/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.T2/PX-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.T2/2N-6000

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 4 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red

PRK18B.1/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 6 m **Design:** Cubic,
Cubic



PRK18B.1/4P-6000

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 6 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK18B.1/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 18B, 18B

Operating range, max.: 0 ... 6 m **Design:** Cubic, Cubic

Light source: LED, Red, LED, Red



PRK318B.W/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4 m **Design:** Cylindrical

Light source: LED, Red



PRK318B.W/4P

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4 m **Design:** Cylindrical

Light source: LED, Red



PRK318B.W/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4 m **Design:** Cylindrical

Light source: LED, Red



PRK318B/4P-M12

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK318B/4P

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK318B/2N-M12

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRK318B/2N

Polarized retro-reflective photoelectric sensor

Series: 318B

Operating range, max.: 0.02 ... 4.5 m **Design:** Cylindrical

Light source: LED, Red



PRKL 8/24.99-S12

Polarized retro-reflective photoelectric sensor

Series: 8

Operating range, max.: 0 ... 12 m **Design:** Cubic

Light source: Laser, Red

PRKL 55/6.22,5000

Polarized retro-reflective photoelectric sensor

Series: 55

Operating range, max.: 0 ... 2 m **Design:** Cubic



PRK 2/42D,150-S12

Polarized retro-reflective photoelectric sensor

Series: 2

Operating range, max.: 0.07 ... 3.5 m **Design:** Cubic

Light source: LED, Red



PRK 2/42D,150-S8

Polarized retro-reflective photoelectric sensor

Series: 2

Operating range, max.: 0.07 ... 3.5 m **Design:** Cubic

Light source: LED, Red



PRK 2/42D

Polarized retro-reflective photoelectric sensor

Series: 2

Operating range, max.: 0.07 ... 3.5 m **Design:** Cubic

Light source: LED, Red



PRK 2/42,150-S12

Polarized retro-reflective photoelectric sensor

Series: 2

Operating range, max.: 0.07 ... 3.5 m **Design:** Cubic

Light source: LED, Red



PRK 2/42,150-S8

Polarized retro-reflective photoelectric sensor

Series: 2

Operating range, max.: 0.07 ... 3.5 m **Design:** Cubic

Light source: LED, Red



PRK 55/6.22,5000

Polarized retro-reflective photoelectric sensor

Series: 55
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK 55/66,5000

Polarized retro-reflective photoelectric sensor

Series: 55
Operating range, max.: 0.2 ... 5 m **Design:** Cubic
Light source: LED, Red



PRK 55/6.002,200-S12

Polarized retro-reflective photoelectric sensor

Series: 55
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRKL 53/6.22-S8

Polarized retro-reflective photoelectric sensor

Series: 53
Operating range, max.: 0 ... 2 m **Design:** Cubic
Light source: Laser, Red



PRK 53/6.22-S8

Polarized retro-reflective photoelectric sensor

Series: 53
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red

PRKL 55/6.22-S8.3

Polarized retro-reflective photoelectric sensor

Series: 55
Operating range, max.: 0 ... 2 m **Design:** Cubic



PRK 96K/R-3428.1-25

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 20 m **Design:** Cubic

Light source: LED, Red



PRK 55/66,200-S12

Polarized retro-reflective photoelectric sensor

Series: 55

Operating range, max.: 0.2 ... 5 m **Design:** Cubic

Light source: LED, Red



PRK 55/66-S8

Polarized retro-reflective photoelectric sensor

Series: 55

Operating range, max.: 0.2 ... 5 m **Design:** Cubic

Light source: LED, Red



PRKL 55/6.22,200-S12

Polarized retro-reflective photoelectric sensor

Series: 55

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRKL 55/6.22-S8

Polarized retro-reflective photoelectric sensor

Series: 55

Operating range, max.: 0 ... 2 m **Design:** Cubic

Light source: Laser, Red



PRK 55/6.22-S8

Polarized retro-reflective photoelectric sensor

Series: 55
Operating range, max.: 0 ... 4 m **Design:** Cubic
Light source: LED, Red



PRK 96M/P-1832-41

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0 ... 7 m **Design:** Cubic
Light source: LED, Red



PRK 96K/R-1420.1-25

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK 96M/P-1361.1-47

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK 96K/P-1360.1-41

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic
Light source: LED, Red

PRK 96M/N-3366-27

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 15 m **Design:** Cubic



PRK 96M/P-1361-47

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK 96M/A-3410-44

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 15 m **Design:** Cubic

Light source: LED, Red



PRK 96M/R-3420-25

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 15 m **Design:** Cubic

Light source: LED, Red



PRK 96M/P-3360-21

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 15 m **Design:** Cubic

Light source: LED, Red



PRK 96M/P-2838-28

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0 ... 7 m **Design:** Cubic

Light source: LED, Red



RK 96K/R-1560-25

Unpolarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 15 m **Design:** Cubic
Light source: LED, Infrared



PRK 96M/P-1362-47

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK 96K/P-1361-29

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK 96M/P-3380-41

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 15 m **Design:** Cubic
Light source: LED, Red



PRK 96M/R-3430-25

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 15 m **Design:** Cubic
Light source: LED, Red

PRK 96K/P-3368-41

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 26 m **Design:** Cubic



IPRK 8/A-S12

Polarized retro-reflective photoelectric sensor

Series: 8
Operating range, max.: 0.1 ... 6.4 m **Design:** Cubic
Light source: LED, Red



PRK 8/66.11-S12

Polarized retro-reflective photoelectric sensor

Series: 8
Operating range, max.: 0 ... 5 m **Design:** Cubic
Light source: LED, Red



PRKL 8/24.91

Polarized retro-reflective photoelectric sensor

Series: 8
Operating range, max.: 0 ... 19 m **Design:** Cubic
Light source: Laser, Red



PRKL 8/24.91-S12

Polarized retro-reflective photoelectric sensor

Series: 8
Operating range, max.: 0 ... 19 m **Design:** Cubic
Light source: Laser, Red



PRK 8/66

Polarized retro-reflective photoelectric sensor

Series: 8
Operating range, max.: 0.1 ... 6.4 m **Design:** Cubic
Light source: LED, Red



PRK 8/44-S12

Polarized retro-reflective photoelectric sensor

Series: 8
Operating range, max.: 0.1 ... 6.4 m **Design:** Cubic
Light source: LED, Red



PRK 96K/R-3428-25

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 20 m **Design:** Cubic
Light source: LED, Red



PRK 96M/P-1400-42

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK 96M/P-1370-42

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic
Light source: LED, Red



PRK 96M/P-1370-22

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic
Light source: LED, Red

PRK 96M/P-1400-22

Polarized retro-reflective photoelectric sensor

Series: 96
Operating range, max.: 0.3 ... 8 m **Design:** Cubic



PRK 96K/R-1430-25

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK 96K/R-1420-25

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK 96K/P-1380-41

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK 96K/P-1360-41

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 8 m **Design:** Cubic

Light source: LED, Red



PRK 96K/P-1360-21

Polarized retro-reflective photoelectric sensor

Series: 96

Operating range, max.: 0.3 ... 8 m **Design:** Cubic

Light source: LED, Red



IPRK 95/44 L.21

Polarized retro-reflective photoelectric sensor

Series: 95
Operating range, max.: 0 ... 4.2 m **Design:** Cubic
Light source: LED, Red



Set PRK5.R3/4P DTKS 30x50

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.1 ... 0.3 m **Design:** Cubic
Light source: LED, Red



PRK5/2

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



SET PRK5/4P-200-M12+BTU200-D10

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



SET PRK5/4P-200-M12+BTU200-D14

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



IPRK 95/44 L.5

Polarized retro-reflective photoelectric sensor

Series: 95
Operating range, max.: 0.15 ... 6 m **Design:** Cubic
Light source: LED, Red



PRK 95/44 L

Polarized retro-reflective photoelectric sensor

Series: 95
Operating range, max.: 0 ... 6 m **Design:** Cubic
Light source: LED, Red



PRK 95/4 L.2

Polarized retro-reflective photoelectric sensor

Series: 95
Operating range, max.: 0 ... 3.4 m **Design:** Cubic
Light source: LED, Red



IPRK 95/44 L.3

Polarized retro-reflective photoelectric sensor

Series: 95
Operating range, max.: 0 ... 0.3 m **Design:** Cubic
Light source: LED, Red



IPRK 95/44 L.2

Polarized retro-reflective photoelectric sensor

Series: 95
Operating range, max.: 0 ... 4.2 m **Design:** Cubic
Light source: LED, Red

PRK5.M3/4P-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic



SET PRK5R34P200M12DTKS30x50

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.1 ... 0.3 m **Design:** Cubic
Light source: LED, Red



PRK5/4X-2000-M8

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



SET PRK5/4P-200-M12+BTU200MVKT

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5/P-200-M8.3

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



Set PRK5.R3/2N DTKS 30x50

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.1 ... 0.3 m **Design:** Cubic
Light source: LED, Red



Set PRK5.R3/2N-M8 DTKS 30x50

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.1 ... 0.3 m **Design:** Cubic
Light source: LED, Red



Set PRK5.R3/4P-M8 DTKS 30x50

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.1 ... 0.3 m **Design:** Cubic
Light source: LED, Red



PRK5/N

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5/P

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5/4X-200-M12

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red

PRK5/2-M8.3

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic



PRK5/4-M8.3

Polarized retro-reflective photoelectric sensor

Series: 5

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5/2X-M8

Polarized retro-reflective photoelectric sensor

Series: 5

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



Set PRK5/4P-M8 + TKS 40x60.A

Polarized retro-reflective photoelectric sensor set

Series: 5

Operating range, max.: 0.02 ... 2.8 m **Design:** Cubic

Light source: LED, Red



PRK5/4X-M8

Polarized retro-reflective photoelectric sensor

Series: 5

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5/4

Polarized retro-reflective photoelectric sensor

Series: 5

Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic

Light source: LED, Red



PRK5.M3/2N

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5.M3/2N-M8

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5.M3/4P

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5.M3/4P-M8

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



SET PRK5 + BT205M + TKS40x60.A

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.02 ... 2.8 m **Design:** Cubic
Light source: LED, Red

SET PRK5+BTU200M+BTU934M

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.02 ... 1.8 m



PRK5/4P-350-M12

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5/4P-800-M12

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



SET PRK5/4P-200-M12+BTU200-D12

Polarized retro-reflective photoelectric sensor set

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5/4-200-M8.3

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red



PRK5/4X-200-M8.1

Polarized retro-reflective photoelectric sensor

Series: 5
Operating range, max.: 0.02 ... 4.5 m **Design:** Cubic
Light source: LED, Red

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>