

Энергетические диффузные датчики

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>



FT28-120F/4P-M12

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.005 ... 0.12 m
Design: Cubic
Light source: LED, Red



ET5BI/4X-M8

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic
Light source: LED, Infrared



ET5BI/4

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic
Light source: LED, Infrared



ET5BI/2

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic
Light source: LED, Infrared



ET5B/PX-200-M12

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic
Light source: LED, Red

ET5B/4X-200-M12

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic



ET5B/4X-M8

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic
Light source: LED, Red



ET5B/2X-M8

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic
Light source: LED, Red



ET5B/4

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic
Light source: LED, Red



ET5B/2

Energetic diffuse sensor

Series: 5B
Operating range, max.: 0.002 ... 0.7 m
Design: Cubic
Light source: LED, Red



FT28.3/PX-200-M8

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.21 m
Design: Cubic
Light source: LED, Red



FT318BI.X3/P4-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.11 m
Design: Cylindrical
Light source: LED, Infrared



FT23/2X-M8

Energetic diffuse sensor

Series: 23
Operating range, max.: 0.005 ... 0.18 m
Design: Cubic
Light source: LED, Red



FT328I.X3/2N-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.11 m
Design: Cylindrical
Light source: LED, Infrared



ET318BI-400F.3/2N

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.4 m
Design: Cylindrical
Light source: LED, Infrared



ET328.W3/4P

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.005 ... 0.35 m
Design: Cylindrical
Light source: LED, Red



FT328I.3/2N-M12P1

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.08 ... 0.1 m
Design: Cylindrical
Light source: LED, Infrared



FT318B.3/2N-5000

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red



ET412B.1/N

Energetic diffuse sensor

Series: 412B
Operating range, max.: 0.004 ... 0.54 m
Design: Cylindrical
Light source: LED, Red



ET412B.1/2

Energetic diffuse sensor

Series: 412B
Operating range, max.: 0.004 ... 0.54 m
Design: Cylindrical
Light source: LED, Red



ET412B.1/NX-M12

Energetic diffuse sensor

Series: 412B
Operating range, max.: 0.004 ... 0.54 m
Design: Cylindrical
Light source: LED, Red

ET412B.1/2X-M12

Energetic diffuse sensor

Series: 412B
Operating range, max.: 0.004 ... 0.54 m
Design: Cylindrical



ET412B.1/P

Energetic diffuse sensor

Series: 412B
Operating range, max.: 0.004 ... 0.54 m
Design: Cylindrical
Light source: LED, Red



ET412B.1/4

Energetic diffuse sensor

Series: 412B
Operating range, max.: 0.004 ... 0.54 m
Design: Cylindrical
Light source: LED, Red



ET412B.1/PX-M12

Energetic diffuse sensor

Series: 412B
Operating range, max.: 0.004 ... 0.54 m
Design: Cylindrical
Light source: LED, Red



ET412B.1/4X-M12

Energetic diffuse sensor

Series: 412B
Operating range, max.: 0.004 ... 0.54 m
Design: Cylindrical
Light source: LED, Red



FT23/4X-M8

Energetic diffuse sensor

Series: 23
Operating range, max.: 0.005 ... 0.18 m
Design: Cubic
Light source: LED, Red



ET23/4X-M8

Energetic diffuse sensor

Series: 23
Operating range, max.: 0 ... 0.56 m
Design: Cubic
Light source: LED, Red



ET23/2X-M8

Energetic diffuse sensor

Series: 23
Operating range, max.: 0 ... 0.56 m
Design: Cubic
Light source: LED, Red



FT23/4

Energetic diffuse sensor

Series: 23
Operating range, max.: 0.005 ... 0.18 m
Design: Cubic
Light source: LED, Red



ET23/4

Energetic diffuse sensor

Series: 23
Operating range, max.: 0 ... 0.56 m
Design: Cubic
Light source: LED, Red



FT23/2

Energetic diffuse sensor

Series: 23
Operating range, max.: 0.005 ... 0.18 m
Design: Cubic
Light source: LED, Red

ET23/2

Energetic diffuse sensor

Series: 23
Operating range, max.: 0 ... 0.56 m
Design: Cubic



FT318BI-100F.X/4P-M12

Energetic diffuse sensor

Series: 318B

Operating range, max.: 0.001 ... 0.1 m

Design: Cylindrical

Light source: LED, Infrared



FT318BI.X3/4P-M12

Energetic diffuse sensor

Series: 318B

Operating range, max.: 0.001 ... 0.11 m

Design: Cylindrical

Light source: LED, Infrared



FT318BI.X3/2N-M12

Energetic diffuse sensor

Series: 318B

Operating range, max.: 0.001 ... 0.11 m

Design: Cylindrical

Light source: LED, Infrared



FT318BI.X3/4P

Energetic diffuse sensor

Series: 318B

Operating range, max.: 0.001 ... 0.11 m

Design: Cylindrical

Light source: LED, Infrared



FT328I.X3/4P-M12

Energetic diffuse sensor

Series: 328

Operating range, max.: 0.001 ... 0.11 m

Design: Cylindrical

Light source: LED, Infrared



FT328I.X3/4P

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.11 m
Design: Cylindrical
Light source: LED, Infrared



FT328I.X3/2N

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.11 m
Design: Cylindrical
Light source: LED, Infrared



FT318BI.X3/2N

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.11 m
Design: Cylindrical
Light source: LED, Infrared



ET328I-400F.3/4P-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.4 m
Design: Cylindrical
Light source: LED, Infrared



ET328I-400F.3/2N-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.4 m
Design: Cylindrical
Light source: LED, Infrared

ET328I-400F.3/2N

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.4 m
Design: Cylindrical



ET328I-400F.3/4P

Energetic diffuse sensor

Series: 328

Operating range, max.: 0.001 ... 0.4 m

Design: Cylindrical

Light source: LED, Infrared



ET318BI.3/2N-M12

Energetic diffuse sensor

Series: 318B

Operating range, max.: 0.001 ... 0.7 m

Design: Cylindrical

Light source: LED, Infrared



ET318BI.3/4P-M12

Energetic diffuse sensor

Series: 318B

Operating range, max.: 0.001 ... 0.7 m

Design: Cylindrical

Light source: LED, Infrared



FT318BI.3/2N-M12

Energetic diffuse sensor

Series: 318B

Operating range, max.: 0.001 ... 0.215 m

Design: Cylindrical

Light source: LED, Infrared



FT318BI.3/4P-M12

Energetic diffuse sensor

Series: 318B

Operating range, max.: 0.001 ... 0.215 m

Design: Cylindrical

Light source: LED, Infrared



FT328I.3/4P-M12P1

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.08 ... 0.1 m
Design: Cylindrical
Light source: LED, Infrared



FT318BI.3/4P

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Infrared



FT318BI.3/2N

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Infrared



ET318BI.3/4P

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Infrared



ET318BI.3/2N

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Infrared

ET328.3/2N

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical



ET328.3/2N-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Red



ET328.3/4P

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Red



ET328.3/4P-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Red



ET328.W3/2N

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.005 ... 0.35 m
Design: Cylindrical
Light source: LED, Red



ET328.W3/2N-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.005 ... 0.35 m
Design: Cylindrical
Light source: LED, Red



ET328.W3/4P-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.005 ... 0.35 m
Design: Cylindrical
Light source: LED, Red



FT328.3/2N

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red



FT328.3/2N-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red



FT328.3/4P

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red



FT328.3/4P-M12

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red

FT328.W3/2N

Energetic diffuse sensor

Series: 328
Operating range, max.: 0.002 ... 0.1 m
Design: Cylindrical



FT328.W3/2N-M12

Energetic diffuse sensor

Series: 328

Operating range, max.: 0.002 ... 0.1 m

Design: Cylindrical

Light source: LED, Red



FT328.W3/4P

Energetic diffuse sensor

Series: 328

Operating range, max.: 0.002 ... 0.1 m

Design: Cylindrical

Light source: LED, Red



FT328.W3/4P-M12

Energetic diffuse sensor

Series: 328

Operating range, max.: 0.002 ... 0.1 m

Design: Cylindrical

Light source: LED, Red



ET28.3/2N

Energetic diffuse sensor

Series: 28

Operating range, max.: 0.001 ... 0.65 m

Design: Cubic

Light source: LED, Red



ET28.3/2N-200-M12

Energetic diffuse sensor

Series: 28

Operating range, max.: 0.001 ... 0.65 m

Design: Cubic

Light source: LED, Red



ET28.3/4P

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.65 m
Design: Cubic
Light source: LED, Red



ET318B.W3/2N

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.005 ... 0.35 m
Design: Cylindrical
Light source: LED, Red



FT318B.W3/4P-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.002 ... 0.1 m
Design: Cylindrical
Light source: LED, Red



RK 93/4-150 L

Energetic diffuse sensor

Series: 93
Operating range, max.: 0.005 ... 0.15 m
Design: Cubic
Light source: LED, Infrared



FT5I.X3/2N

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.1 m
Design: Cubic
Light source: LED, Infrared



ET28.3/4P-200-M12

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.65 m
Design: Cubic
Light source: LED, Red



ET28.3/4P-M12

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.65 m
Design: Cubic
Light source: LED, Red



FT28.3/2N

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.21 m
Design: Cubic
Light source: LED, Red



FT28.3/2N-M12

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.21 m
Design: Cubic
Light source: LED, Red



FT28.3/4P

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.21 m
Design: Cubic
Light source: LED, Red

FT28.3/4P-200-M12

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.21 m
Design: Cubic



FT28.3/4P-M12

Energetic diffuse sensor

Series: 28
Operating range, max.: 0.001 ... 0.21 m
Design: Cubic
Light source: LED, Red



ET318B.3/2N

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Red



ET318B.3/2N-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Red



ET318B.3/4P

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Red



ET318B.3/4P-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.7 m
Design: Cylindrical
Light source: LED, Red



ET318B.W3/2N-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.005 ... 0.35 m
Design: Cylindrical
Light source: LED, Red



ET318B.W3/4P

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.005 ... 0.35 m
Design: Cylindrical
Light source: LED, Red



ET318B.W3/4P-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.005 ... 0.35 m
Design: Cylindrical
Light source: LED, Red



FT318B.3/2N

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red

FT318B.3/2N-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red



FT318B.3/4P

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red



FT318B.3/4P-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.001 ... 0.215 m
Design: Cylindrical
Light source: LED, Red



FT318B.W3/2N

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.002 ... 0.1 m
Design: Cylindrical
Light source: LED, Red



FT318B.W3/2N-M12

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.002 ... 0.1 m
Design: Cylindrical
Light source: LED, Red



FT318B.W3/4P

Energetic diffuse sensor

Series: 318B
Operating range, max.: 0.002 ... 0.1 m
Design: Cylindrical
Light source: LED, Red



RK 93/4-200 L

Energetic diffuse sensor

Series: 93
Operating range, max.: 0.002 ... 0.2 m
Design: Cubic
Light source: LED, Infrared



RK 93/4-60 L

Energetic diffuse sensor

Series: 93
Operating range, max.: 0 ... 0.06 m
Design: Cubic
Light source: LED, Infrared



ET5I.3/4P-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Infrared



FT5I.3/4P-200-M8P1

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.08 ... 0.12 m
Design: Cubic
Light source: LED, Infrared



ET5.3/2-M8.3

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Red

ET5.3/4-M8.3

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic



FT5.3/2-M8.3

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Red



FT5.3/4-M8.3

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Red



FT5I.X3/4P-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.1 m
Design: Cubic
Light source: LED, Infrared



FT5I.X3/2N-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.1 m
Design: Cubic
Light source: LED, Infrared



FT5I.X3/4P

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.1 m
Design: Cubic
Light source: LED, Infrared



FT5I.3/2N-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Infrared



FT5I.3/4P-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Infrared



FT5I.3/4P-200-M12P1

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.08 ... 0.12 m
Design: Cubic
Light source: LED, Infrared



FT5I.3/4P

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Infrared



FT5I.3/2N

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Infrared

ET5I.3/4P

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.11 ... 0.7 m
Design: Cubic



ET5I.3/2N

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Infrared



SET ET5 + BT205M

Energetic diffuse sensor set

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Red



ET5.3/2N-200-M12

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Red



ET5.3/2N

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Red



ET5.3/2N-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Red



ET5.3/4P

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Red



ET5.3/4P-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Red



FT5.3/2N-200-M12

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Red



FT5.3/2N

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Red



FT5.3/2N-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Red

FT5.3/4P-200-M12

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic



FT5.3/4P

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Red



FT5.3/4P-M8

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.215 m
Design: Cubic
Light source: LED, Red



RTL 318M/P-300-S12

Energetic diffuse sensor

Series: 318
Operating range, max.: 0 ... 0.3 m
Design: Cylindrical
Light source: Laser, Red



ET5.3/4P-200-M12

Energetic diffuse sensor

Series: 5
Operating range, max.: 0.001 ... 0.7 m
Design: Cubic
Light source: LED, Red

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>