

Световые завесы CSL 505

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>



CSL505-T25-1475-M8-D6

Light curtain transmitter

Measurement field length: 1,475 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1475-M8

Light curtain receiver

Measurement field length: 1,475 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-188-VB-M8

Light curtain transmitter

Measurement field length: 187.5 mm

Beam spacing: 12.5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-188-VB-M8

Light curtain receiver

Measurement field length: 187.5 mm

Beam spacing: 12.5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T100-3100-M8

Light curtain transmitter

Measurement field length: 3,100 mm

Beam spacing: 100 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R100-3100-M8

Light curtain receiver

Measurement field length: 3,100 mm
Beam spacing: 100 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T100-2700-M8

Light curtain transmitter

Measurement field length: 2,700 mm
Beam spacing: 100 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R100-2700-M8

Light curtain receiver

Measurement field length: 2,700 mm
Beam spacing: 100 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T100-2300-M8

Light curtain transmitter

Measurement field length: 2,300 mm
Beam spacing: 100 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R100-2300-M8

Light curtain receiver

Measurement field length: 2,300 mm
Beam spacing: 100 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T100-1900-M8

Light curtain transmitter

Measurement field length: 1,900 mm
Beam spacing: 100 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R100-1900-M8

Light curtain receiver

Measurement field length: 1,900 mm
Beam spacing: 100 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T100-1500-M8

Light curtain transmitter

Measurement field length: 1,500 mm
Beam spacing: 100 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R100-1500-M8

Light curtain receiver

Measurement field length: 1,500 mm
Beam spacing: 100 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T100-1100-M8

Light curtain transmitter

Measurement field length: 1,100 mm
Beam spacing: 100 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R100-1100-M8

Light curtain receiver

Measurement field length: 1,100 mm
Beam spacing: 100 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T100-700-M8

Light curtain transmitter

Measurement field length: 700 mm

Beam spacing: 100 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R100-700-M8

Light curtain receiver

Measurement field length: 700 mm

Beam spacing: 100 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T50-3150-M8

Light curtain transmitter

Measurement field length: 3,150 mm

Beam spacing: 50 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R50-3150-M8

Light curtain receiver

Measurement field length: 3,150 mm

Beam spacing: 50 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T50-2750-M8

Light curtain transmitter

Measurement field length: 2,750 mm

Beam spacing: 50 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R50-2750-M8

Light curtain receiver

Measurement field length: 2,750 mm
Beam spacing: 50 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T50-2350-M8

Light curtain transmitter

Measurement field length: 2,350 mm
Beam spacing: 50 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R50-2350-M8

Light curtain receiver

Measurement field length: 2,350 mm
Beam spacing: 50 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-R25-1675-M8

Light curtain receiver

Measurement field length: 1,675 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1575-M8

Light curtain transmitter

Measurement field length: 1,575 mm
Beam spacing: 25 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1575-M8

Light curtain receiver

Measurement field length: 1,575 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T50-1950-M8

Light curtain transmitter

Measurement field length: 1,950 mm
Beam spacing: 50 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R50-1950-M8

Light curtain receiver

Measurement field length: 1,950 mm
Beam spacing: 50 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T50-1550-M8

Light curtain transmitter

Measurement field length: 1,550 mm
Beam spacing: 50 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R50-1550-M8

Light curtain receiver

Measurement field length: 1,550 mm
Beam spacing: 50 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T50-1150-M8

Light curtain transmitter

Measurement field length: 1,150 mm
Beam spacing: 50 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R50-1150-M8

Light curtain receiver

Measurement field length: 1,150 mm

Beam spacing: 50 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T50-750-M8

Light curtain transmitter

Measurement field length: 750 mm

Beam spacing: 50 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R50-750-M8

Light curtain receiver

Measurement field length: 750 mm

Beam spacing: 50 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T50-350-M8

Light curtain transmitter

Measurement field length: 350 mm

Beam spacing: 50 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R50-350-M8

Light curtain receiver

Measurement field length: 350 mm

Beam spacing: 50 mm

Special version: Parallel-beam scanning,



CSL505-T25-2375-M8

Light curtain transmitter

Measurement field length: 2,375 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-R25-2375-M8

Light curtain receiver

Measurement field length: 2,375 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-2175-M8

Light curtain transmitter

Measurement field length: 2,175 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-R25-2175-M8

Light curtain receiver

Measurement field length: 2,175 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1975-M8

Light curtain transmitter

Measurement field length: 1,975 mm
Beam spacing: 25 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1975-M8

Light curtain receiver

Measurement field length: 1,975 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1875-M8

Light curtain transmitter

Measurement field length: 1,875 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1875-M8

Light curtain receiver

Measurement field length: 1,875 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1775-M8

Light curtain transmitter

Measurement field length: 1,775 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1775-M8

Light curtain receiver

Measurement field length: 1,775 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1675-M8

Light curtain transmitter

Measurement field length: 1,675 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-T25-1475-M8

Light curtain transmitter

Measurement field length: 1,475 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1475-M8

Light curtain receiver

Measurement field length: 1,475 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1375-M8

Light curtain transmitter

Measurement field length: 1,375 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1375-M8

Light curtain receiver

Measurement field length: 1,375 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1275-M8

Light curtain transmitter

Measurement field length: 1,275 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1275-M8

Light curtain receiver

Measurement field length: 1,275 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1175-M8

Light curtain transmitter

Measurement field length: 1,175 mm
Beam spacing: 25 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1175-M8

Light curtain receiver

Measurement field length: 1,175 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-1075-M8

Light curtain transmitter

Measurement field length: 1,075 mm
Beam spacing: 25 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-1075-M8

Light curtain receiver

Measurement field length: 1,075 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-975-M8

Light curtain transmitter

Measurement field length: 975 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-975-M8

Light curtain receiver

Measurement field length: 975 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-875-M8

Light curtain transmitter

Measurement field length: 875 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-875-M8

Light curtain receiver

Measurement field length: 875 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-775-M8

Light curtain transmitter

Measurement field length: 775 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-775-M8

Light curtain receiver

Measurement field length: 775 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-675-M8

Light curtain transmitter

Measurement field length: 675 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-675-M8

Light curtain receiver

Measurement field length: 675 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-575-M8

Light curtain transmitter

Measurement field length: 575 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-575-M8

Light curtain receiver

Measurement field length: 575 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-475-M8

Light curtain transmitter

Measurement field length: 475 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-475-M8

Light curtain receiver

Measurement field length: 475 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-375-M8

Light curtain transmitter

Measurement field length: 375 mm
Beam spacing: 25 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-375-M8

Light curtain receiver

Measurement field length: 375 mm
Beam spacing: 25 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-R12.5-188-M8

Light curtain receiver

Measurement field length: 188 mm
Beam spacing: 12.5 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-88-M8

Light curtain transmitter

Measurement field length: 88 mm
Beam spacing: 12.5 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-88-M8

Light curtain receiver

Measurement field length: 88 mm
Beam spacing: 12.5 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-275-M8

Light curtain transmitter

Measurement field length: 275 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-275-M8

Light curtain receiver

Measurement field length: 275 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T25-175-M8

Light curtain transmitter

Measurement field length: 175 mm

Beam spacing: 25 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R25-175-M8

Light curtain receiver

Measurement field length: 175 mm

Beam spacing: 25 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-988-M8

Light curtain transmitter

Measurement field length: 987.5 mm

Beam spacing: 12.5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-988-M8

Light curtain receiver

Measurement field length: 987.5 mm
Beam spacing: 12.5 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-888-M8

Light curtain transmitter

Measurement field length: 887.5 mm
Beam spacing: 12.5 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-888-M8

Light curtain receiver

Measurement field length: 887.5 mm
Beam spacing: 12.5 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-788-M8

Light curtain transmitter

Measurement field length: 788 mm
Beam spacing: 12.5 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-788-M8

Light curtain receiver

Measurement field length: 788 mm
Beam spacing: 12.5 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-688-M8

Light curtain transmitter

Measurement field length: 688 mm

Beam spacing: 12.5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-688-M8

Light curtain receiver

Measurement field length: 688 mm

Beam spacing: 12.5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-588-M8

Light curtain transmitter

Measurement field length: 588 mm

Beam spacing: 12.5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-588-M8

Light curtain receiver

Measurement field length: 588 mm

Beam spacing: 12.5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-488-M8

Light curtain transmitter

Measurement field length: 488 mm

Beam spacing: 12.5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-488-M8

Light curtain receiver

Measurement field length: 488 mm

Beam spacing: 12.5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-388-M8

Light curtain transmitter

Measurement field length: 388 mm

Beam spacing: 12.5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-388-M8

Light curtain receiver

Measurement field length: 388 mm

Beam spacing: 12.5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-288-M8

Light curtain transmitter

Measurement field length: 288 mm

Beam spacing: 12.5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R12.5-288-M8

Light curtain receiver

Measurement field length: 288 mm

Beam spacing: 12.5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T12.5-188-M8

Light curtain transmitter

Measurement field length: 188 mm

Beam spacing: 12.5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-T05-395-M8

Light curtain transmitter

Measurement field length: 395 mm

Beam spacing: 5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-395-M8

Light curtain receiver

Measurement field length: 395 mm

Beam spacing: 5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-355-M8

Light curtain transmitter

Measurement field length: 355 mm

Beam spacing: 5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-355-M8

Light curtain receiver

Measurement field length: 355 mm

Beam spacing: 5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-315-M8

Light curtain transmitter

Measurement field length: 315 mm

Beam spacing: 5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-315-M8

Light curtain receiver

Measurement field length: 315 mm

Beam spacing: 5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-275-M8

Light curtain transmitter

Measurement field length: 275 mm

Beam spacing: 5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-275-M8

Light curtain receiver

Measurement field length: 275 mm

Beam spacing: 5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-235-M8

Light curtain transmitter

Measurement field length: 235 mm

Beam spacing: 5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-235-M8

Light curtain receiver

Measurement field length: 235 mm

Beam spacing: 5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-195-M8

Light curtain transmitter

Measurement field length: 195 mm
Beam spacing: 5 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-195-M8

Light curtain receiver

Measurement field length: 195 mm
Beam spacing: 5 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-155-M8

Light curtain transmitter

Measurement field length: 155 mm
Beam spacing: 5 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par



CSL505-R05-155-M8

Light curtain receiver

Measurement field length: 155 mm
Beam spacing: 5 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-115-M8

Light curtain transmitter

Measurement field length: 115 mm
Beam spacing: 5 mm
Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-115-M8

Light curtain receiver

Measurement field length: 115 mm
Beam spacing: 5 mm
Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-75-M8

Light curtain transmitter

Measurement field length: 75 mm

Beam spacing: 5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-75-M8

Light curtain receiver

Measurement field length: 75 mm

Beam spacing: 5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...



CSL505-T05-35-M8

Light curtain transmitter

Measurement field length: 35 mm

Beam spacing: 5 mm

Special version: Diagonal-beam scanning,
Crossed-beam scanning, Par...



CSL505-R05-35-M8

Light curtain receiver

Measurement field length: 35 mm

Beam spacing: 5 mm

Special version: Parallel-beam scanning,
Crossed-beam scanning, Dia...

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>