

Световые завесы для взрывозащищенных применений

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>



CML720i-T10-460.A-M12-EX

Light curtain transmitter

Measurement field length: 460 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-460.A/CN-M12-EX

Light curtain receiver

Measurement field length: 460 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-140.A-M12-EX

Light curtain transmitter

Measurement field length: 140 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-140.A/CN-M12-EX

Light curtain receiver

Measurement field length: 140 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-300.A-M12-EX

Light curtain transmitter

Measurement field length: 300 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-300.A/CN-M12-EX

Light curtain receiver

Measurement field length: 300 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-620.A-M12-EX

Light curtain transmitter

Measurement field length: 620 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-620.A/CN-M12-EX

Light curtain receiver

Measurement field length: 620 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-780.A-M12-EX

Light curtain transmitter

Measurement field length: 780 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-780.A/CN-M12-EX

Light curtain receiver

Measurement field length: 780 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-940.A-M12-EX

Light curtain transmitter

Measurement field length: 940 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-940.A/CN-M12-EX

Light curtain receiver

Measurement field length: 940 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-1100.A-M12-EX

Light curtain transmitter

Measurement field length: 1,100 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-1100.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,100 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-1260.A-M12-EX

Light curtain transmitter

Measurement field length: 1,260 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-1260.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,260 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-1420.A-M12-EX

Light curtain transmitter

Measurement field length: 1,420 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-1420.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,420 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-1580.A-M12-EX

Light curtain transmitter

Measurement field length: 1,580 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-1580.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,580 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-1740.A-M12-EX

Light curtain transmitter

Measurement field length: 1,740 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-1740.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,740 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-1900.A-M12-EX

Light curtain transmitter

Measurement field length: 1,900 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-1900.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,900 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-1410.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,410 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-1570.A-M12-EX

Light curtain transmitter

Measurement field length: 1,570 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-1570.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,570 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-2060.A-M12-EX

Light curtain transmitter

Measurement field length: 2,060 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-2060.A/CN-M12-EX

Light curtain receiver

Measurement field length: 2,060 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T10-2220.A-M12-EX

Light curtain transmitter

Measurement field length: 2,220 mm **Beam spacing:** 10 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R10-2220.A/CN-M12-EX

Light curtain receiver

Measurement field length: 2,220 mm **Beam spacing:** 10 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-130.A-M12-EX

Light curtain transmitter

Measurement field length: 130 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-130.A/CN-M12-EX

Light curtain receiver

Measurement field length: 130 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-290.A-M12-EX

Light curtain transmitter

Measurement field length: 290 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-290.A/CN-M12-EX

Light curtain receiver

Measurement field length: 290 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-450.A-M12-EX

Light curtain transmitter

Measurement field length: 450 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-450.A/CN-M12-EX

Light curtain receiver

Measurement field length: 450 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-610.A-M12-EX

Light curtain transmitter

Measurement field length: 610 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-610.A/CN-M12-EX

Light curtain receiver

Measurement field length: 610 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-770.A-M12-EX

Light curtain transmitter

Measurement field length: 770 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-770.A/CN-M12-EX

Light curtain receiver

Measurement field length: 770 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-930.A-M12-EX

Light curtain transmitter

Measurement field length: 930 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-930.A/CN-M12-EX

Light curtain receiver

Measurement field length: 930 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-1090.A-M12-EX

Light curtain transmitter

Measurement field length: 1,090 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-1090.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,090 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-1250.A-M12-EX

Light curtain transmitter

Measurement field length: 1,250 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-1250.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,250 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-1410.A-M12-EX

Light curtain transmitter

Measurement field length: 1,410 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-1730.A-M12-EX

Light curtain transmitter

Measurement field length: 1,730 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-1730.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,730 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-1890.A-M12-EX

Light curtain transmitter

Measurement field length: 1,890 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-1890.A/CN-M12-EX

Light curtain receiver

Measurement field length: 1,890 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-2050.A-M12-EX

Light curtain transmitter

Measurement field length: 2,050 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-2050.A/CN-M12-EX

Light curtain receiver

Measurement field length: 2,050 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-T20-2210.A-M12-EX

Light curtain transmitter

Measurement field length: 2,210 mm **Beam spacing:** 20 mm
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML720i-R20-2210.A/CN-M12-EX

Light curtain receiver

Measurement field length: 2,210 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...



CML730i-T20-450.A-M12-67

Light curtain transmitter

Measurement field length: 450 mm, 450 mm **Beam spacing:** 20 mm, 20 mm
Special version: Diagonal-beam scanning, Crossed-beam scanning, Par...



CML720i-R20-450.A/CN-M12-EX

Light curtain receiver

Measurement field length: 450 mm **Beam spacing:** 20 mm
Interface: CANopen, IO-Link
Special version: Crossed-beam scanning, Diagonal-beam scanning, Ex-...

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>