

Световые завесы для быстрых и прозрачных приложений

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>

For fast and transparent applications

These measuring light curtains have integrated interfaces and their innovative plug outlets ensure gapless object tracing. They offer operating ranges of up to 8 m and a unique measurement cycle of 10 μ s per beam. In addition, even transparent objects up to 3.5 m are reliably detected. Sturdy metal housing also for use in rough industrial environments. Connection via M12 connector for fast installation.



CML730i-T10-480.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 480 mm

Beam spacing: 10 mm



CML730i-R10-480.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 480 mm

Beam spacing: 10 mm



CML730i-R05-2160.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,160 mm

Beam spacing: 5 mm



CML730i-R20-1430.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,430 mm

Beam spacing: 20 mm



CML730i-T10-1920.R-M12

- Light curtain transmitter

Series: 730

Measurement field length: 1,920 mm

Beam spacing: 10 mm



CML730i-R10-1920.R/L-M12

- Light curtain receiver

Series: 730

Measurement field length: 1,920 mm

Beam spacing: 10 mm



CML730i-T10-1920.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 1,920 mm

Beam spacing: 10 mm



CML730i-R10-1920.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 1,920 mm

Beam spacing: 10 mm



CML730i-T05-160.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 160 mm

Beam spacing: 5 mm



CML730i-R05-160.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 160 mm

Beam spacing: 5 mm



CML730i-T05-240.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 240 mm

Beam spacing: 5 mm



CML730i-R05-240.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 240 mm

Beam spacing: 5 mm



CML730i-T05-320.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 320 mm

Beam spacing: 5 mm



CML730i-R05-320.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 320 mm

Beam spacing: 5 mm



CML730i-T05-400.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 400 mm

Beam spacing: 5 mm



CML730i-R05-400.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 400 mm

Beam spacing: 5 mm



CML730i-T05-480.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 480 mm

Beam spacing: 5 mm



CML730i-R05-480.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 480 mm

Beam spacing: 5 mm



CML730i-T05-560.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 560 mm

Beam spacing: 5 mm



CML730i-R05-560.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 560 mm

Beam spacing: 5 mm



CML730i-T05-640.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 640 mm

Beam spacing: 5 mm



CML730i-R05-640.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 640 mm

Beam spacing: 5 mm



CML730i-T05-720.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 720 mm

Beam spacing: 5 mm



CML730i-R05-720.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 720 mm

Beam spacing: 5 mm



CML730i-T05-800.A-M12

- Light curtain transmitter

Series: 730

Measurement field length: 800 mm

Beam spacing: 5 mm



CML730i-R05-800.A/CN-M12

- Light curtain receiver

Series: 730

Measurement field length: 800 mm

Beam spacing: 5 mm



CML730i-R05-1760.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,760 mm

Beam spacing: 5 mm



CML730i-T05-880.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 880 mm

Beam spacing: 5 mm



CML730i-R05-880.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 880 mm

Beam spacing: 5 mm



CML730i-T05-960.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 960 mm

Beam spacing: 5 mm



CML730i-R05-960.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 960 mm

Beam spacing: 5 mm



CML730i-T05-1040.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,040 mm

Beam spacing: 5 mm



CML730i-T05-1120.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 5 mm



CML730i-R05-1120.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 5 mm



CML730i-T05-1200.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,200 mm

Beam spacing: 5 mm



CML730i-R05-1200.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,200 mm
Beam spacing: 5 mm



CML730i-T05-1280.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,280 mm
Beam spacing: 5 mm



CML730i-R05-1280.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,280 mm
Beam spacing: 5 mm



CML730i-T05-1360.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,360 mm
Beam spacing: 5 mm



CML730i-R05-1360.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,360 mm
Beam spacing: 5 mm



CML730i-T05-1440.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,440 mm

Beam spacing: 5 mm



CML730i-R05-1440.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,440 mm

Beam spacing: 5 mm



CML730i-T05-1520.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,520 mm

Beam spacing: 5 mm



CML730i-R05-1520.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,520 mm

Beam spacing: 5 mm



CML730i-T05-1600.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,600 mm

Beam spacing: 5 mm



CML730i-R05-1600.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,600 mm

Beam spacing: 5 mm



CML730i-T05-1680.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,680 mm

Beam spacing: 5 mm



CML730i-R05-1680.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,680 mm

Beam spacing: 5 mm



CML730i-T05-1760.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,760 mm

Beam spacing: 5 mm



CML730i-T05-1840.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,840 mm

Beam spacing: 5 mm



CML730i-R05-1840.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,840 mm

Beam spacing: 5 mm



CML730i-T05-1920.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,920 mm

Beam spacing: 5 mm



CML730i-R05-1920.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,920 mm

Beam spacing: 5 mm



CML730i-T05-2000.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,000 mm

Beam spacing: 5 mm



CML730i-T05-2080.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,080 mm

Beam spacing: 5 mm



CML730i-R05-2080.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,080 mm

Beam spacing: 5 mm



CML730i-T05-2160.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,160 mm

Beam spacing: 5 mm



CML730i-R05-2160.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,160 mm

Beam spacing: 5 mm



CML730i-T05-2240.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,240 mm

Beam spacing: 5 mm



CML730i-R05-2240.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,240 mm

Beam spacing: 5 mm



CML730i-T05-2320.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,320 mm

Beam spacing: 5 mm



CML730i-R05-2320.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,320 mm

Beam spacing: 5 mm



CML730i-T05-2400.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,400 mm

Beam spacing: 5 mm



CML730i-R05-2400.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,400 mm

Beam spacing: 5 mm



CML730i-T05-2480.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,480 mm

Beam spacing: 5 mm



CML730i-R05-2480.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,480 mm

Beam spacing: 5 mm



CML730i-T05-2560.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,560 mm

Beam spacing: 5 mm



CML730i-R05-2560.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,560 mm

Beam spacing: 5 mm



CML730i-T05-2640.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,640 mm

Beam spacing: 5 mm



CML730i-R05-2640.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,640 mm

Beam spacing: 5 mm



CML730i-T05-2720.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,720 mm

Beam spacing: 5 mm



CML730i-R05-2720.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,720 mm
Beam spacing: 5 mm



CML730i-R10-1600.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,600 mm
Beam spacing: 10 mm



CML730i-R20-790.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 790 mm
Beam spacing: 20 mm



CML730i-R20-2710.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,710 mm
Beam spacing: 20 mm



CML730i-R05-240.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 240 mm
Beam spacing: 5 mm



CML730i-T05-2800.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,800 mm

Beam spacing: 5 mm



CML730i-R05-2800.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,800 mm

Beam spacing: 5 mm



CML730i-T05-2880.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,880 mm

Beam spacing: 5 mm



CML730i-R05-2880.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,880 mm

Beam spacing: 5 mm



CML730i-T05-2960.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,960 mm

Beam spacing: 5 mm



CML730i-T10-160.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 160 mm

Beam spacing: 10 mm



CML730i-R10-160.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 160 mm

Beam spacing: 10 mm



CML730i-T10-320.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 320 mm

Beam spacing: 10 mm



CML730i-R10-320.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 320 mm
Beam spacing: 10 mm



CML730i-T10-640.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 640 mm
Beam spacing: 10 mm



CML730i-R10-640.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 640 mm
Beam spacing: 10 mm



CML730i-T10-800.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 800 mm
Beam spacing: 10 mm



CML730i-R10-800.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 800 mm
Beam spacing: 10 mm



CML730i-T10-960.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 960 mm

Beam spacing: 10 mm



CML730i-R10-960.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 960 mm

Beam spacing: 10 mm



CML730i-T10-1120.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 10 mm



CML730i-R10-1120.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 10 mm



CML730i-T10-1280.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,280 mm

Beam spacing: 10 mm



CML730i-R10-1280.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,280 mm

Beam spacing: 10 mm



CML730i-T10-1440.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,440 mm

Beam spacing: 10 mm



CML730i-R10-1440.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,440 mm

Beam spacing: 10 mm



CML730i-T10-1600.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,600 mm

Beam spacing: 10 mm



CML730i-T10-1760.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,760 mm

Beam spacing: 10 mm



CML730i-R10-1760.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,760 mm

Beam spacing: 10 mm



CML730i-T10-2080.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,080 mm

Beam spacing: 10 mm



CML730i-R10-2080.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,080 mm

Beam spacing: 10 mm



CML730i-R05-1200.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,200 mm

Beam spacing: 5 mm



CML730i-T10-2240.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,240 mm

Beam spacing: 10 mm



CML730i-T10-2400.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,400 mm

Beam spacing: 10 mm



CML730i-R10-2400.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,400 mm

Beam spacing: 10 mm



CML730i-T10-2560.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,560 mm

Beam spacing: 10 mm



CML730i-R10-2560.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,560 mm
Beam spacing: 10 mm



CML730i-T10-2720.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 2,720 mm
Beam spacing: 10 mm



CML730i-R10-2720.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,720 mm
Beam spacing: 10 mm



CML730i-T10-2880.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 2,880 mm
Beam spacing: 10 mm



CML730i-R10-2880.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,880 mm
Beam spacing: 10 mm



CML730i-T20-150.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 150 mm

Beam spacing: 20 mm



CML730i-R20-150.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 150 mm

Beam spacing: 20 mm



CML730i-T20-310.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 310 mm

Beam spacing: 20 mm



CML730i-R20-310.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 310 mm

Beam spacing: 20 mm



CML730i-T20-470.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 470 mm

Beam spacing: 20 mm



CML730i-R20-470.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 470 mm
Beam spacing: 20 mm



CML730i-T20-630.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 630 mm
Beam spacing: 20 mm



CML730i-R20-630.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 630 mm
Beam spacing: 20 mm



CML730i-T20-790.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 790 mm
Beam spacing: 20 mm



CML730i-T20-950.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 950 mm

Beam spacing: 20 mm



CML730i-R20-950.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 950 mm

Beam spacing: 20 mm



CML730i-T20-1110.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,110 mm

Beam spacing: 20 mm



CML730i-R20-1110.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,110 mm

Beam spacing: 20 mm



CML730i-T20-1270.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,270 mm

Beam spacing: 20 mm



CML730i-T20-1430.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,430 mm

Beam spacing: 20 mm



CML730i-R20-1430.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,430 mm

Beam spacing: 20 mm



CML730i-T20-1590.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,590 mm

Beam spacing: 20 mm



CML730i-R20-1590.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,590 mm
Beam spacing: 20 mm



CML730i-T20-1750.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,750 mm
Beam spacing: 20 mm



CML730i-R20-1750.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,750 mm
Beam spacing: 20 mm



CML730i-T20-1910.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,910 mm
Beam spacing: 20 mm



CML730i-R20-1910.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,910 mm
Beam spacing: 20 mm



CML730i-T20-2070.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,070 mm

Beam spacing: 20 mm



CML730i-R20-2070.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,070 mm

Beam spacing: 20 mm



CML730i-T20-2230.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,230 mm

Beam spacing: 20 mm



CML730i-R20-2230.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,230 mm

Beam spacing: 20 mm



CML730i-T20-2390.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,390 mm

Beam spacing: 20 mm



CML730i-R20-2390.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,390 mm

Beam spacing: 20 mm



CML730i-T20-2550.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,550 mm

Beam spacing: 20 mm



CML730i-R20-2550.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,550 mm

Beam spacing: 20 mm



CML730i-T20-2710.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,710 mm

Beam spacing: 20 mm



CML730i-T20-2870.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,870 mm

Beam spacing: 20 mm



CML730i-R20-2870.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,870 mm

Beam spacing: 20 mm



CML730i-T40-290.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 290 mm

Beam spacing: 40 mm



CML730i-R40-290.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 290 mm

Beam spacing: 40 mm



CML730i-T40-610.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 610 mm

Beam spacing: 40 mm



CML730i-T40-930.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 930 mm

Beam spacing: 40 mm



CML730i-R40-930.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 930 mm

Beam spacing: 40 mm



CML730i-T40-1250.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,250 mm

Beam spacing: 40 mm



CML730i-R40-1250.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,250 mm
Beam spacing: 40 mm



CML730i-T40-1570.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,570 mm
Beam spacing: 40 mm



CML730i-R40-1570.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,570 mm
Beam spacing: 40 mm



CML730i-T40-1890.A-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,890 mm
Beam spacing: 40 mm



CML730i-R40-1890.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,890 mm
Beam spacing: 40 mm



CML730i-T40-2210.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,210 mm

Beam spacing: 40 mm



CML730i-R40-2210.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,210 mm

Beam spacing: 40 mm



CML730i-T40-2530.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,530 mm

Beam spacing: 40 mm



CML730i-R40-2530.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,530 mm

Beam spacing: 40 mm



CML730i-T40-2850.A-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,850 mm

Beam spacing: 40 mm



CML730i-R40-2850.A/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,850 mm

Beam spacing: 40 mm



CML730i-T05-160.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 160 mm

Beam spacing: 5 mm



CML730i-R05-160.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 160 mm

Beam spacing: 5 mm



CML730i-T05-240.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 240 mm

Beam spacing: 5 mm



CML730i-T05-320.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 320 mm

Beam spacing: 5 mm



CML730i-R05-320.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 320 mm

Beam spacing: 5 mm



CML730i-T05-400.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 400 mm

Beam spacing: 5 mm



CML730i-R05-400.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 400 mm

Beam spacing: 5 mm



CML730i-T05-480.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 480 mm
Beam spacing: 5 mm



CML730i-T05-560.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 560 mm
Beam spacing: 5 mm



CML730i-R05-560.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 560 mm
Beam spacing: 5 mm



CML730i-T05-640.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 640 mm
Beam spacing: 5 mm



CML730i-R05-640.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 640 mm
Beam spacing: 5 mm



CML730i-T05-720.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 720 mm
Beam spacing: 5 mm



CML730i-R05-720.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 720 mm
Beam spacing: 5 mm



CML730i-T05-800.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 800 mm
Beam spacing: 5 mm



CML730i-R05-800.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 800 mm
Beam spacing: 5 mm



CML730i-T05-880.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 880 mm
Beam spacing: 5 mm



CML730i-R05-880.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 880 mm
Beam spacing: 5 mm



CML730i-T05-960.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 960 mm
Beam spacing: 5 mm



CML730i-R05-960.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 960 mm
Beam spacing: 5 mm



CML730i-T05-1040.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,040 mm
Beam spacing: 5 mm



CML730i-R05-1040.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,040 mm

Beam spacing: 5 mm



CML730i-T05-1120.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 5 mm



CML730i-R05-1120.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 5 mm



CML730i-T05-1200.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,200 mm

Beam spacing: 5 mm



CML730i-T05-1280.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,280 mm

Beam spacing: 5 mm



CML730i-R05-1280.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,280 mm

Beam spacing: 5 mm



CML730i-T05-1360.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,360 mm

Beam spacing: 5 mm



CML730i-R05-1360.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,360 mm

Beam spacing: 5 mm



CML730i-T05-1440.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,440 mm

Beam spacing: 5 mm



CML730i-T05-1520.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,520 mm

Beam spacing: 5 mm



CML730i-R05-1520.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,520 mm

Beam spacing: 5 mm



CML730i-T05-1600.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,600 mm

Beam spacing: 5 mm



CML730i-R05-1600.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,600 mm

Beam spacing: 5 mm



CML730i-T05-1680.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,680 mm

Beam spacing: 5 mm



CML730i-R05-1680.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,680 mm

Beam spacing: 5 mm



CML730i-T05-1760.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,760 mm

Beam spacing: 5 mm



CML730i-R05-1760.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,760 mm

Beam spacing: 5 mm



CML730i-T05-1840.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,840 mm

Beam spacing: 5 mm



CML730i-R05-1840.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,840 mm

Beam spacing: 5 mm



CML730i-T05-1920.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,920 mm

Beam spacing: 5 mm



CML730i-R05-1920.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,920 mm

Beam spacing: 5 mm



CML730i-T05-2000.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,000 mm

Beam spacing: 5 mm



CML730i-R05-2000.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,000 mm

Beam spacing: 5 mm



CML730i-T05-2080.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,080 mm

Beam spacing: 5 mm



CML730i-R05-2080.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,080 mm

Beam spacing: 5 mm



CML730i-T05-2160.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,160 mm

Beam spacing: 5 mm



CML730i-T05-2240.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,240 mm

Beam spacing: 5 mm



CML730i-R05-2240.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,240 mm

Beam spacing: 5 mm



CML730i-T05-2320.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,320 mm

Beam spacing: 5 mm



CML730i-R05-2320.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,320 mm

Beam spacing: 5 mm



CML730i-T05-2400.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,400 mm

Beam spacing: 5 mm



CML730i-T05-2480.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,480 mm

Beam spacing: 5 mm



CML730i-R05-2480.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,480 mm

Beam spacing: 5 mm



CML730i-T05-2560.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,560 mm

Beam spacing: 5 mm



CML730i-R05-2560.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,560 mm
Beam spacing: 5 mm



CML730i-T05-2640.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 2,640 mm
Beam spacing: 5 mm



CML730i-R05-2640.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,640 mm
Beam spacing: 5 mm



CML730i-T05-2720.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 2,720 mm
Beam spacing: 5 mm



CML730i-R05-2720.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,720 mm
Beam spacing: 5 mm



CML730i-T05-2800.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,800 mm

Beam spacing: 5 mm



CML730i-R05-2800.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,800 mm

Beam spacing: 5 mm



CML730i-T05-2880.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,880 mm

Beam spacing: 5 mm



CML730i-R05-2880.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,880 mm

Beam spacing: 5 mm



CML730i-T05-2960.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,960 mm

Beam spacing: 5 mm



CML730i-R05-2960.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,960 mm

Beam spacing: 5 mm



CML730i-T10-160.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 160 mm

Beam spacing: 10 mm



CML730i-R10-160.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 160 mm

Beam spacing: 10 mm



CML730i-T10-320.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 320 mm

Beam spacing: 10 mm



CML730i-R10-320.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 320 mm

Beam spacing: 10 mm



CML730i-T10-480.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 480 mm

Beam spacing: 10 mm



CML730i-R10-480.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 480 mm

Beam spacing: 10 mm



CML730i-T10-640.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 640 mm

Beam spacing: 10 mm



CML730i-R10-640.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 640 mm

Beam spacing: 10 mm



CML730i-T10-800.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 800 mm

Beam spacing: 10 mm



CML730i-T10-960.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 960 mm

Beam spacing: 10 mm



CML730i-R10-960.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 960 mm

Beam spacing: 10 mm



CML730i-T10-1120.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 10 mm



CML730i-R10-1120.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,120 mm
Beam spacing: 10 mm



CML730i-T10-1280.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,280 mm
Beam spacing: 10 mm



CML730i-R10-1280.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,280 mm
Beam spacing: 10 mm



CML730i-T10-1440.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 1,440 mm
Beam spacing: 10 mm



CML730i-R10-1440.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,440 mm
Beam spacing: 10 mm



CML730i-T10-1600.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,600 mm

Beam spacing: 10 mm



CML730i-R10-1600.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,600 mm

Beam spacing: 10 mm



CML730i-T10-1760.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,760 mm

Beam spacing: 10 mm



CML730i-R10-1760.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,760 mm

Beam spacing: 10 mm



CML730i-T10-2080.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,080 mm

Beam spacing: 10 mm



CML730i-R10-2080.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,080 mm

Beam spacing: 10 mm



CML730i-T10-2240.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,240 mm

Beam spacing: 10 mm



CML730i-R10-2240.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,240 mm

Beam spacing: 10 mm



CML730i-T10-2400.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,400 mm

Beam spacing: 10 mm



CML730i-R10-2400.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,400 mm

Beam spacing: 10 mm



CML730i-T10-2560.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,560 mm

Beam spacing: 10 mm



CML730i-R10-2560.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,560 mm

Beam spacing: 10 mm



CML730i-T10-2720.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,720 mm

Beam spacing: 10 mm



CML730i-R10-2720.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,720 mm

Beam spacing: 10 mm



CML730i-T10-2880.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,880 mm

Beam spacing: 10 mm



CML730i-T20-150.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 150 mm

Beam spacing: 20 mm



CML730i-R20-150.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 150 mm

Beam spacing: 20 mm



CML730i-T20-310.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 310 mm

Beam spacing: 20 mm



CML730i-R20-310.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 310 mm
Beam spacing: 20 mm



CML730i-T20-470.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 470 mm
Beam spacing: 20 mm



CML730i-R20-470.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 470 mm
Beam spacing: 20 mm



CML730i-T20-630.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 630 mm
Beam spacing: 20 mm



CML730i-R20-630.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 630 mm
Beam spacing: 20 mm



CML730i-T20-790.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 790 mm

Beam spacing: 20 mm



CML730i-R20-790.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 790 mm

Beam spacing: 20 mm



CML730i-T20-950.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 950 mm

Beam spacing: 20 mm



CML730i-R20-950.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 950 mm

Beam spacing: 20 mm



CML730i-T20-1110.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,110 mm

Beam spacing: 20 mm



CML730i-R20-1110.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,110 mm

Beam spacing: 20 mm



CML730i-T20-1270.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,270 mm

Beam spacing: 20 mm



CML730i-R20-1270.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,270 mm

Beam spacing: 20 mm



CML730i-T20-1430.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,430 mm

Beam spacing: 20 mm



CML730i-T20-1590.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,590 mm

Beam spacing: 20 mm



CML730i-R20-1590.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,590 mm

Beam spacing: 20 mm



CML730i-T20-1750.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,750 mm

Beam spacing: 20 mm



CML730i-R20-1750.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,750 mm

Beam spacing: 20 mm



CML730i-T20-1910.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,910 mm

Beam spacing: 20 mm



CML730i-T20-2070.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,070 mm

Beam spacing: 20 mm



CML730i-R20-2070.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,070 mm

Beam spacing: 20 mm



CML730i-T20-2230.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,230 mm

Beam spacing: 20 mm



CML730i-R20-2230.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,230 mm
Beam spacing: 20 mm



CML730i-T20-2390.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 2,390 mm
Beam spacing: 20 mm



CML730i-R20-2390.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,390 mm
Beam spacing: 20 mm



CML730i-T20-2550.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 2,550 mm
Beam spacing: 20 mm



CML730i-R20-2550.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 2,550 mm
Beam spacing: 20 mm



CML730i-T20-2710.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,710 mm

Beam spacing: 20 mm



CML730i-R20-2710.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,710 mm

Beam spacing: 20 mm



CML730i-T20-2870.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,870 mm

Beam spacing: 20 mm



CML730i-R20-2870.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,870 mm

Beam spacing: 20 mm



CML730i-T40-290.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 290 mm

Beam spacing: 40 mm



CML730i-R40-290.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 290 mm
Beam spacing: 40 mm



CML730i-T40-610.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 610 mm
Beam spacing: 40 mm



CML730i-R40-610.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 610 mm
Beam spacing: 40 mm



CML730i-T40-930.R-M12

Light curtain transmitter

Series: 730
Measurement field length: 930 mm
Beam spacing: 40 mm



CML730i-R40-930.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 930 mm
Beam spacing: 40 mm



CML730i-T40-1250.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,250 mm

Beam spacing: 40 mm



CML730i-R40-1250.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,250 mm

Beam spacing: 40 mm



CML730i-T40-1570.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,570 mm

Beam spacing: 40 mm



CML730i-R40-1570.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 1,570 mm

Beam spacing: 40 mm



CML730i-T40-1890.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,890 mm

Beam spacing: 40 mm



CML730i-T40-2210.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,210 mm

Beam spacing: 40 mm

Part no.: 50118990



CML730i-R40-2210.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,210 mm

Beam spacing: 40 mm



CML730i-T40-2530.R-M12

Light curtain transmitter

Series: 730

Measurement field length: 2,530 mm

Beam spacing: 40 mm



CML730i-R40-2530.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,850 mm

Beam spacing: 40 mm



CML730i-R40-2850.R/CN-M12

Light curtain receiver

Series: 730

Measurement field length: 2,850 mm

Beam spacing: 40 mm



CML730i-T05-160.A-PS-M12

Watch/inquiry list
Light curtain transmitter

Series: 730

Measurement field length: 160 mm

Beam spacing: 5 mm



CML730i-T05-240.A-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 240 mm

Beam spacing: 5 mm



CML730i-R05-240.A/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 240 mm



CML730i-T05-320.A-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 320 mm

Beam spacing: 5 mm



CML730i-R05-320.A/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 320 mm

Beam spacing: 5 mm



CML730i-T05-480.A-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 480 mm

Beam spacing: 5 mm



CML730i-R05-480.A/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 480 mm

Beam spacing: 5 mm



CML730i-T05-640.A-PS-M12

Series: 730

Measurement field length: 640 mm

Beam spacing: 5 mm



CML730i-R05-640.A/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 640 mm

Beam spacing: 5 mm



CML730i-T05-800.A-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 800 mm

Beam spacing: 5 mm



CML730i-R05-800.A/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 800 mm

Beam spacing: 5 mm



CML730i-T05-960.A-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 960 mm

Beam spacing: 5 mm



CML730i-R05-960.A/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 960 mm

Beam spacing: 5 mm



CML730i-T05-1120.A-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 5 mm



CML730i-R05-1120.A/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 5 mm



CML730i-T05-1280.A-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,280 mm

Beam spacing: 5 mm



CML730i-R05-160.R/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 160 mm



CML730i-R05-1280.A/CV-PS-M12

CML730i-T05-160.R-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 160 mm

Beam spacing: 5 mm



CML730i-R05-320.R/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 320 mm

Beam spacing: 5 mm



CML730i-R05-240.R/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 240 mm

Beam spacing: 5 mm



CML730i-T05-320.R-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 320 mm

Beam spacing: 5 mm



CML730i-T05-480.R-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 480 mm

Beam spacing: 5 mm



CML730i-R05-480.R/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 480 mm

Beam spacing: 5 mm



CML730i-T05-800 .R-PS-M12

Measurement field length: 800 mm

Beam spacing: 5 mm



CML730i-T05-640.R-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 640 mm

Beam spacing: 5 mm



CML730i-T05-960.R-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 960 mm

Beam spacing: 5 mm



CML730i-R05-800.R/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 800 mm

Beam spacing: 5 mm



CML730i-T05-1120.R-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 5 mm



CML730i-R05-960.R/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 960 mm

Beam spacing: 5 mm



CML730i-R05-1120.R/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 1,120 mm

Beam spacing: 5 mm



CML730i-T05-1280.R-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 1,280 mm

Beam spacing: 5 mm



CML730i-R05-1280.R/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 1,280 mm

Beam spacing: 5 mm



CML730i-T05-400.R-PS-M12

Light curtain transmitter

Watch/inquiry list

Series: 730

Measurement field length: 400 mm

Beam spacing: 5 mm

[Request quotation](#)



CML730i-T05-400.A-PS-M12

Light curtain transmitter

Series: 730

Measurement field length: 400 mm

Beam spacing: 5 mm



CML730i-R05-400.A/CV-PS-M12

Light curtain receiver

Series: 730

Measurement field length: 400 mm

Beam spacing: 5 mm



CML730i-R05-400.R/CV-PS-M12

Light curtain receiver



CML730i-R20-450.A/CV-M12-67

Light curtain receiver

Series: 730

Measurement field length: 450 mm

Beam spacing: 20 mm



CML730i-T20-450.A-M12-67

Light curtain transmitter

Series: 720, 720

Measurement field length: 450 mm, 450 mm

Beam spacing: 20 mm, 20 mm



CML720i-R20-450.A/CN-M12-EX

Light curtain receiver

Series: 720

Measurement field length: 450 mm

Beam spacing: 20 mm



CML730i-T20-450.R-M12-67

Light curtain transmitter

Series: 730

Measurement field length: 450 mm

Beam spacing: 20 mm



CML730i-R20-450.R/CV-M12-67

Light curtain receiver

Series: 730

Measurement field length: 450 mm

Beam spacing: 20 mm



CML730i-T40-1530.R-M12-67

Light curtain transmitter

Series: 730

Measurement field length: 1,570 mm

Beam spacing: 40 mm



CML730i-R40-1570.R/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,570 mm
Beam spacing: 40 mm



CML730i-R20-1090.A/L-M12-67

Light curtain receiver

Series:
Measurement field length: 1,110 mm
Beam spacing: 20 mm



CML730i-T20-1090.A-M12-67

Light curtain transmitter

Series: 730
Measurement field length: 1,110 mm
Beam spacing: 20 mm



CML730i-R20-1110.A/CN-M12

Light curtain receiver

Series: 730
Measurement field length: 1,110 mm
Beam spacing: 20 mm

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ezu@nt-rt.ru || сайт: <https://leuze.nt-rt.ru/>